

Specification	
Part No.	LKV314HDR-V3.0
Technical	
Input	HDMI×1(Type A, 19 pin, female)
Output	HDMI×4(Type A, 19 pin, female)
Input cable length	≤5m(AWG26 HDMI cable support HDMI2.0)
Output cable length	≤5m(AWG26 HDMI cable support HDMI2.0)
Video support	480i@60Hz、480p@60Hz、 576i@50Hz、576p@50Hz、 720p@50/60Hz、1080i@50/60Hz、 1080p@50/60Hz、4K×2K@24/25/30/60Hz
Max.transmission rate	18Gbps
Audio format	7.1/5.1/2.1 CH Dolby Digital,DTS-HD and Dolby TrueHD Audio
TMDS signal	0.5~1.5Vp-p(TMDS)
DDC signal	5Vp-p(TTL)
EDID passthrough	Yes, support downscaling
HDR	Yes
HDMI	HDMI2.0
HDCP	HDCP2.2, HDCP1.4
Mechanical	
Housing	Iron
Dimensions(L×W×H mm)	158(L) × 80(W) × 17(H) mm
Net weight	200g
Color	Black
Power supply	5V/1A
Power consumption	<3W
Operation temperature	0~60℃
Storage temperature	-20~70℃
Relative humidity	20-90% (no condensation)

SHENZHEN LENKENG TECHNOLOGY CO.,LTD.