

## Noise tester NF-562

### Item Specifics:

Is\_customized: **Yes**

Brand Name: **Noyafa**

Model Number: **NF-562S**

Place of Origin: **Shenzhen.China**

Main function: testing noise

Color: **Black**

Power: **1.5V AAA\*4pcs**

Warranty: **1Year**

### Introduction:

NF-562S is a professional noise tester with portable size, stable functionality,the device can direct, accurate and fast test the decibel level in any environment; Mainly used in construction field,entertainment venue, living community ect to monitor the noise level of the environment.

### Technical indexes:

|                      |                 |
|----------------------|-----------------|
| Product Name         | Noise tester    |
| Product Model        | NF-562S         |
| Product Size         | 227*63.4*31mm   |
| Battery              | 1.5V AAA*4pcs   |
| Display              | 4-digit display |
| Sampling frequency   | 500ms           |
| Weighting properties | A / C           |

|                        |                              |                                          |
|------------------------|------------------------------|------------------------------------------|
| Sensor                 | Capacitive Microphone        |                                          |
| Noise testing          | Testing range                | 30~130dBA<br>35~130dBC                   |
|                        | Testing Accuracy             | ± 1.5dB(94dB@1KHz)<br>± 5dB(94dB@8KHz)   |
|                        | Range level                  | 30~80dB,60~110dB,80~130dB,30~130dB(AUTO) |
|                        | Resolution                   | 0.1dB                                    |
| Testing speed          | Fast                         | 125ms                                    |
|                        | Slow                         | 1s                                       |
| Over/Under range       | √                            |                                          |
| MAX/MIN testing        | √                            |                                          |
| Auto-off               | 20 minutes without operation |                                          |
| Data Hold              | √                            |                                          |
| LCD backlight          | √                            |                                          |
| Low battery indication | √                            |                                          |
| Working temperature    | 0~40°C                       |                                          |
| Working humidity       | 10~80%RH                     |                                          |
| Storage temoerature    | -10~60°C                     |                                          |
| Storage humidity       | 10~70%RH                     |                                          |