

JVCU360 360° Meeting Webcam - Product Specifications

Host Connector: USB-C® / USB™ 2.0 Type-A

Image Sensor: 1/2.9" CMOS Sensor

LED Indicators:

- Red: Muted
- Blue: Power on

Mounting Style: N/A

Operating Voltage and Current: DC 5V / 500 mA ±15 mA

Privacy Cover: No

Protocol: UVC 1.1 & UAC

Shutter Style: N/A

Warranty: 1-Year Limited Warranty

Performance

Display FOV:

- Full Screen Mode: 180° (H), 53° (V)
- 360° All Around View Mode: 360° (H), 53° (V)
- Host Mode: 360° (H), 120° (H), 53° (V)
- Dual Host Mode: 360° (H), 60° (H), 53° (V)
- Single View Mode: 90° (H), 58.5° (V)
- Wide Angle View Mode: 120° (H), 88.6° (V)

Effective Pixels:

- Full Screen Mode: 1920 (H) x 540 (V)
- 360° All Around View Mode: 1920 (H) x 720 (V)
- Host Mode: 1920 (H) x 270 (V), 1920 (H) x 810 (V)
- Dual Host Mode: 1920 (H) x 270 (V), 960 (H) x 810 (V)
- Single View Mode: 1920 (H) x 1080 (V)
- Wide Angle View Mode: 120° (H), 88.6° (V)

Frame Rate: 30 FPS

Max Display Refresh Rate: 30 Hz

Megapixels: 2 million pixels (2MP)

Microphone: Built-in omnidirectional microphone

Output Format: MJPEG

Supported Resolution - Output:

- 1920 x 1080
- 1280 x 720
- 640 x 480 / 360

Physical Specifications

Cable Length: 9.84 ft. (300 cm)

Color Options: White, Black

Enclosure Type: ABS

Lens Kit: N/A

Operating Humidity: < 90% non-condensing

Operating Temperature: 41°F to 104°F (0°C to 40°C)

Product Depth: 1.46 in. (3.7 cm)

Product Height: 7.6 in. (19.3 cm)

Product Weight: ~12.35 oz (350g)

Product Width: 3.68 in. (9.35 cm)

Storage Humidity: < 90% non-condensing

Storage Temperature: -4°F to 140°F (-20°C to 60°C)

Package Contents

1 - JVCU360 360° Meeting Webcam

1 - Quick Installation Guide