Hardware
host connector
HDMI™ male
infared
N/A
led indicators
N/A
ports
N/A
power source
USB™ micro-B to USB™ Type-A male
warranty
1 Year Limited
Performance
audio channel
2.1 via HDMI™
esd protection
N/A
hdcp compliance
N/A
hdmi compliance
HDMI™ v1.4
infared return frequency
N/A
ovp protection

```
N/A
rf output power
N/A
security - encryption
WPA2
supported resolution - output
3840 x 2160
1920 × 1080
1280 × 720
    Physical Specifications
cable length
39 in. (100 cm)
color
White
connector type
Plastic
operating humidity
< 85% non-condensing
operating temperature
+14 to +104°F (-10 to +40°C)
product depth
0.43 in. (11 mm)
product height
3.74 in. (95 mm)
product weight
```

2.8 oz (79.5g)

product width

1.25 in. (32 mm)

storage humidity

< 85% non-condensing

storage temperature

-4 to +122°F (-20 to +50°C)

Wireless Protocols

antenna type: External antenna

channel width: 20 MHz, 40 MHz

Frequency: 2.4 GHz, 5 GHz

Range: Up to 10 -15 meters

Standard: IEEE 802.11ac

Package Contents

- 1 JVAW76 ScreenCast 4K Wireless Display Adapter
- 1 External antenna with USB™ Type-A power cable (39")
- 1 HDMI™ extension cable (5.11")
- 1 Quick Installation Guide (QIG)

System Requirements

Windows® 10 / 8.1

Android[™] 4.0 or later

macOS® 10.15 or later with AirPlay® Support

iOS® 10.0 or later

iPadOS® 13 or later

Chrome OS™

Special Notes

• Intended to be used with an external wireless display