

Hardware	
Warranty	2 Year Limited
Host Connector	USB-C® Male
Video Output	2 - HDMI™ Female
Power Source	Bus-powered
Network Interface	RJ45 (Gigabit Ethernet)
Audio Supported	Yes
Ports	• 1 - USB-C® Power Delivery 3.0 • 3 - USB™ 3.0 Type-A • 1 - 4K HDMI™ • 1 - 2K/1080p HDMI™ • 1 - SD™ & microSD™ memory card reader/writer • 1 - RJ45 Gigabit Ethernet • 1 - 3.5 mm combo audio jack
Performance	
Maximum Display Resolution	Dual Displays: 3840 x 2160 and 2048 x 1152 / 1920 x 1080 Single Display: 3840 x 2160

Maximum Display Refresh Rate	4K @ 30 Hz 2K @ 60 Hz
Maximum Data Transfer Rate	5 Gbps
Displays Supported	2
Compatible Networks	10/100/1000 Mbps
Audio Channel	2.1 via HDMI™ / 3.5 mm Aux
Power	
Power Delivery	Up to 100W via USB-C®
Power Consumption	≤ 900 mA
Input Current	Up to 5A
Input Voltage	Up to 20V
Output Current	Up to 5A
Output Voltage	Up to 20V
Physical Specifications	
Color	Grey & Black
Enclosure Type	Aluminum

Cable Length	1.48 ft (45 cm)
Product Height	0.87 in. (21.98 mm)
Product Width	3.25 in. (82.46 mm)
Product Depth	13.79 in. (350.18 mm)
Product Weight	10.79 oz (306 g)
Storage Temperature	14 to 149°F (-10 to 65°C)
Storage Humidity	< 85% non-condensing
Operating Temperature	32 to 118°F (0 to 48°C)
Operating Humidity	< 85% non-condensing

System Requirements

- Microsoft® Windows® 10 or later
macOS® 10.14 or later
- Intel® HD Graphics 4000/ ATI™ HD 7xxx/ NVIDIA® 5XXM or higher
- Available USB-C® port that supports DisplayPort™ Alt Mode and USB™ Power Delivery 2.0 or 3.0
Please refer to the manufacturer of your computer for more information about your device
- Extended Monitor: (More powerful processors recommended for multiple displays)

- • One 2K (2048 x 1152 @ 60 Hz) full-screen video playback
 - CPU: Intel® Core™ i5 Quad Core
 - RAM: 4 GB memory or higher
- • Two 2K (2048 x 1152 @ 60 Hz) full-screen video playback
 - CPU: Intel® Core™ i7 Quad Core
 - RAM: 8 GB memory or higher

Special Notes

- A 4K-capable display is required for obtaining the 3840 x 2160 resolution
 - If connected to a USB™ 2.0 host port, or if using a USB™ 2.0 host cable, performance may be limited
 - The dock can connect to a USB-C® port that doesn't support Power Delivery but it will not pass power through the connected device
 - If you are using a high-powered USB™ device, attach a USB-C® power adapter to the power delivery port for optimal performance
 - To ensure files copy completely, do not remove the USB-C® power adapter while copying files. For maximum performance, use a computer and USB-C® power adapter equipped with PD 3.0
 - We advise no more than one (1) bus-powered/portable external hard disk drive to be connected to the USB™ hub at a time
-

Package Contents

- 1 - JCD542 USB-C® Dual HDMI™ Docking Station
 - 1 - Quick Installation Guide (QIG)
-

Special Notes

- Driver installation is required for macOS® and Windows®. If the computer has network access and administrative rights, Windows® can automatically install the driver when the device is plugged in.