Data Sheet

Acer Type-C Universal Docking Station 15 in 1





Perfect Solution

Featuring high-speed USB, SD/microSD card readers, 8K resolution-capable video output, Gigabit Ethernet and audio combo jack, simply connect a USB-C power adapter for fast charging.

Fast charging

Supporting up to 100 W of Power Delivery, it offers continuous power to host devices while transferring files or streaming media, without worrying about running out of battery.

Multiple ports

Equipped with 5x USB-A, 1x USB-C of which 2xUSB-A 2.0, 2xUSB-A 3.2 Gen1, 1xUSB-A 3.2 Gen2,1xUSB-C Gen2 ports, supporting up to 10Gb/s super speed data transfer. SD and microSD card readers, dual HDMI and a DisplayPort video output, Gigabit Ethernet and 3.5 mm audio combo jack. It is the ideal partner for your office and entertainment

© Copyright 2025 Acer Inc.

Data Sheet | Acer Type-C Universal Docking Station 15 in 1



Specifications

Host interface	USB-C	**Audio**	1x 3.5 mm combo
Compatibility	Windows, ChromeOS, macOS	**SD / microSD**	3.0 Version
Power Delivery	USB-C Up to 100 W (power adapter not included)		
USB	1 x USB-C 10Gb/s 1 x USB-A 10Gb/s 2x USB-A 5Gb/s 2x USB-A 480Mb/s	**Operating environment temperature**	0~40°C
		Color	Silver Grey
Video	2x HDMI 4K@60Hz Max 1x Display Port 8K@30Hz Max	**Dimensions**	162.3(L)*60(W)*60(H) mm
RJ45	1x 1 Gb/s	**Weight**	300g
Additional	Supports vPro/AMT		

Video output resolution

Windows DP 1.4 with DSC	**HDMI1**	**HDMI2**	**Display Port**
Single Video Output	3840x2160@60Hz	3840x2160@60Hz	7680×4320@30HZ
Dual Video Output	3840x2160@60Hz	3840x2160@60Hz	
		3840x2160@60Hz	3840x2160@60Hz
	3840x2160@60Hz		3840x2160@60Hz
Triple Video Output	3840x2160@60Hz	3840x2160@30Hz	3840x2160@30Hz
Windows DP 1.4 without DSC	**HDMI**	**HDMI**	**DisplayPort**
Single Video Output	3840x2160@60Hz	3840x2160@60Hz	3840x2160@60Hz
Dual Video Output	3840x2160@30Hz	3840x2160@30Hz	
		3840x2160@30Hz	3840x2160@30Hz
	3840x2160@30Hz		3840x2160@30Hz
Triple Video Output	1920x1080@60Hz	1920x1080@60Hz	1920x1080@60Hz
Windows DP 1.2	**HDMI**	**HDMI**	**Display Port**
Single Video Output	3840x2160@30Hz	3840x2160@30Hz	3840x2160@30Hz
Dual Video Output	1920x1080@60Hz	1920x1080@60Hz	
		1920x1080@60Hz	1920x1080@60Hz
	1920x1080@60Hz		1920x1080@60Hz
Triple Video Output	1920x1080@60Hz	1920x1080@60Hz	1920x1080@60Hz
macOS DP 1.4	**HDMI**	**HDMI**	**Display Port**
Single Video Output	3840x2160@60Hz	3840x2160@60Hz	3840x2160@60Hz
Dual Video Output	3840x2160@60Hz	3840x2160@60Hz	
		3840x2160@60Hz	3840x2160@60Hz
	3840x2160@60Hz		3840x2160@60Hz
Dual Video Output	3840x2160@60Hz	3840x2160@60Hz	3840x2160@60Hz
macOS DP 1.2	**HDMI**	**HDMI**	**Display Port**
Single Video Output	3840x2160@30Hz	3840x2160@30Hz	3840x2160@30Hz
Dual Video Output	3840x2160@30Hz	3840x2160@30Hz	
		3840x2160@30Hz	3840x2160@30Hz
	3840x2160@30Hz		3840x2160@30Hz
Dual Video Output	3840x2160@30Hz	3840x2160@30Hz	3840x2160@30Hz

The maximum display numbers, resolutions and refresh rates may vary depending on the specifications and capabilities of your connected host laptops and monitors.

© Copyright 2025 Acer Inc.